

Address: No.7, Xiyi street, South of Xingfa Road, Wusha Liwu No.6 District, Chang'an town, Dongguan City, China
Tel:0769-33360095 Tax:0769-81882595-8008

Web: www.chinayihui.en.alibaba.com Email: jackzeng@chinayihui.net

CPJ-3000 Series Profile Projector



Product Description

Vertical Profile Projector is a photoelectric measuring system of high precision and efficiency. It can inspect all kinds of surface and outline of the complicated work pieces such as cam, template, tread, gear, perform willing cutter and so on. The measurement data can be printed and output. It requires in the checking department and workshop and is widely used machinery, mould, tool, meter, and light industry.

Address: No.7, Xiyi street, South of Xingfa Road, Wusha Liwu No.6 District, Chang'an town, Dongguan City, China
Tel:0769-33360095 Tax:0769-81882595-8008

Tel:0769-33360095 Tax:0769-81882595-800 Web: www.chinayihui.en.alibaba.com Email: jackzeng@chinayihui.net

Technical Parameters

| Model | | CPJ-3015 | CPJ-3020 | CPJ-3025 |
|----------------------|---|------------|----------|----------|
| Worktable | Metal table's size(mm) | 340*152 | 404*228 | 450*280 |
| | Glass table's size(mm) | 196*96 | 260 *160 | 306 *196 |
| | X-axis Stroke(mm) | 150 | 200 | 250 |
| | Y-axis Stroke(mm) | 50 | 100 | 150 |
| | Z-axis Stroke(mm) | 90 focus | 90 focus | 90 focus |
| | Measuring accuracy(μm) | 3+L/200 | 3+L/200 | 3+L/200 |
| | (L unit: mm) | | | |
| | Resolution(X,Y axis):0.001mm | | | |
| Projector screen | Screen size (mm):Ø 312 | | | |
| | Used range>Ø 300 | | | |
| | Screen rotary range: 0°~360° | | | |
| | Reversed image | | | |
| | Resolution(X-axis,Y-axis):1' or 0.01° | | | |
| Lens | Lens multiple: 10X(option) 20X(option) 50X(option) 100X(option) | | | |
| | Object view(mm): | Ø30 Ø15 Ø6 | Ø3 | |
| | Working distance(mm): 77.7 44.3 38.4 25.3 | | | |
| Data | DC-3000 multi-function data processing system, can realize the transition of English and | | | |
| Processing System | Chinese, it can be used to gather the data and measure the point, line, circle, angle and distance. | | | |
| Illumination | The illumination of transmission and reflection: 24V/150W-halogen lamp. | | | |
| Power | 110V/220V(AC), 50/60HZ, Total power:400W | | | |
| Cooling | Forced cooling | | | |